TECHNICAL DATA SHEET ITEM CODE PPA HT 32 my

HIGH TACK ADHESIVE TAPE FOR MEDIUM WEIGHT PACKAGING

MAIN APPLICATIONS

PRODUCT DESCRIPTION

No noise adhesive tape with solvent-free water-based acrylic adhesive. Characterized by the high tack formula. Suitable for medium weight box sealing with manual dispensers or automatic carton sealing machines. Resistant to UV rays and natural ageing.

FEATURES



to ET version = easy tear.

WATER BASED ACRYLIC

| TECHNICAL DATA | Metric | Values | Test method |
|---------------------|--------|--------|-------------|
| Backing thickness | μm | 32 | AFERA 5006 |
| Total thickness | μm | 56 | AFERA 5006 |
| Adhesion to steel | N/cm | 2.6 | AFERA 5001 |
| Tensile strength | N/cm | 50 | AFERA 5004 |
| Elongation at break | % | 160 | AFERA 5004 |

Technical Informations, storage and product use

The product must be used within 12 months from the delivery date (6 months if jumbo). It is advisable to keep the material in its original packaging, away from heat sources and away from direct light. The storage temperature must be between 15° and 30° C and the relative humidity between 40 and 60%. For storage temperatures other than those indicated, recondition the product to the levels described above. The technical data shown in the data sheets are the average of the analyzes obtained on normal production. Aging can determine the variation of some technical and aesthetic characteristics of the product within the time limits indicated above without affecting its quality and functionality. The technical data shown are reported with a tolerance of +/- 10% and may be modified at any time for production needs or technical updates.

expotape declines all responsibility for direct damage and for the consequences deriving from improper use of the product. It is advisable to check the conformity of the product in relation to the specific conditions of use. Rev.01_31/03/2022



TRANSPARENT